



# TRIAX

connecting the future

TDS 65A RAL 7016, singlepack

Art. Number 120500



**TRIAX TD Dishes** The difference is clear

Manufactured and tested to the highest standards of precision and quality, TRIAX's easy-to-install dishes offer outstanding performance, durability and reliability.

TDS: Steel TDA: Aluminium

- Unrivalled build quality, whether Steel or Aluminium
  - Hot-dip galvanized steel OR long lasting Aluminium - for extra corrosion protection
  - TRIAX's unique cable protection system
  - Every part, every accessory is weatherproofed
  - 2 years corrosion warranty
  - 5 years functionality warranty
- Outstanding performance
  - High gain for an exceptional signal
- Quick and easy installation
  - One-click mounting system
  - Self-locking screw & nuts
- Logistic friendly
  - Single or Bulk packaging, according to customer needs

TRIAX is your reliable partner, with comprehensive service and support.

[Click here](#) to see our guide on how to install TRIAX satellite dishes.

## Technical Specifications

### ORDER INFORMATION

EAN Number 5702661205002



## Technical Specifications

### CHARACTERISTICS

|                     |           |
|---------------------|-----------|
| F/D ratio           | 0,62      |
| G/T LNB 0.7   dB/K  | 16.0 dB/K |
| X-polarisation   dB | ≤ -25 dB  |
| Offset angle   °    | 26 °      |
| Elevation range   ° | 0...90 °  |

### FREQUENCY RANGE

|                       |                  |
|-----------------------|------------------|
| Frequency range   GHz | 10.7...12.75 GHz |
|-----------------------|------------------|

### GAIN

|                       |        |
|-----------------------|--------|
| Gain @ 11.7 GHz   dBi | 36 dBi |
|-----------------------|--------|

### MECHANICAL

|                            |                            |
|----------------------------|----------------------------|
| Height (cm)   cm           | 66 cm                      |
| Width (cm)   cm            | 60 cm                      |
| LNB holder                 | 40                         |
| Mast bracket diameter   mm | 30...60 mm                 |
| Reflector type             | Offset                     |
| Beamwidth   °              | 3.1 °                      |
| Main material              | Galvanized steel (hot-dip) |
| Arm Colour                 | Raw                        |
| Colour                     | RAL 7016 - Anthracite grey |
| Packing QTY                | 1                          |
| Packaging Height   m       | 0.734 m                    |
| Packaging Width   m        | 0.684 m                    |
| Packaging Depth   m        | 0.100 m                    |
| Packaging Volume   m3      | 0.050 m3                   |
| Net Weight   kg            | 3.220 kg                   |
| Tara Weight   kg           | 1.050 kg                   |
| Total Weight   kg          | 4.270 kg                   |